

Dingli BT22RT

Diesel boom lift

The **Dingli BT22RT** boasts **power to platform, robust design and smooth operation**. With it's **rough-terrain capabilities and four-wheel drive and steer**, it's ideal for construction, maintenance and other tasks on challenging ground conditions.

Machine specification

Working height: 22.51m
Horizontal outreach: 17.28m
Safe working load: 454kg
Closed length: 9.82m
Closed height: 2.7m

Closed neight. 2.7mClosed width: 2.5m

• Platform size: 2.44m x 0.91m

Weight: 13,000kgRotation: Continuous

Power: Diesel

• **IPAF licence type:** 3b

Ground condition: Rough terrain (4-wheel drive & steer)

• Boom type: Telescopic

• People on platform: 3 maximum

Outdoor use: YesPower to platform: Yes

Generator: Yes

Key benefits

 SkySentry telematics to allow you to track machine location, review machine utilisation statistics and monitor and control access as required.

• For increased safety when working at height, this machine is **fitted with** the manufacturer's secondary guarding system.

 Fitted with Harness ON™, an intelligent anchor point that stops the MEWP's operation until the operator attaches their harness carabiner.



Interested in hiring this machine? Contact our friendly team by calling 0345 745 0000 or emailing ncc@nationwideplatforms.co.uk.